

# PT20 - PT22S (D)

Ratings @ 0.8 PF		Prime Rating	Stand-by Rating
Voltage* <sup>1</sup>	Frequency* <sup>2</sup>	PT 20* <sup>3</sup>	PT 22S* <sup>4</sup>
230/400 V	50 Hz	20 KVA	21.5 KVA
277/480 V	60 Hz	23 KVA	25 KVA

The above ratings represent the generating set capability guaranteed within ±3% at the reference conditions equivalent to those specified in ISO 8528/1.



## Notes

1. The applicable voltage range is 380V to 415V for 50Hz, and 380V to 480V for 60Hz applications. For other voltage consult factory.

2. This generating set is of switchable speed of 1500rpm or 1800rpm.

3. PT20 is the prime power rating of the generating set, where a variable load and unlimited hours usage are applied on the generating set with an average load factor of 80% of the prime rating over each 24 hour period. Noting that a 10% overload is available for 1 hour in every 12 hours operation.

4. PT22S is the standby power rating of the generating set, where a variable load limited to an annual usage up to 500 hours is applied, with 300 hours of which may be continuous running. Noting that no overload is permitted.

## Certifications



- The complete Generating Set is type-tested according to ISO 8528-8 Standard.



- The control panel is certified by an ISO 17025 accredited laboratory to have IP55 according to IEC 60355



Quality ISO 9001 SAI GLOBAL

## Dimensions

<b>Length</b>	1500 mm
<b>Width</b>	610 mm
<b>Height</b>	1000 mm
<b>Weight</b>	485 Kg

## Technical Data

Engine model	Perkins 404D-22G	
Cylinders	4 vertical in-line	
Aspiration	Naturally aspirated Indirect	
Combustion	injection	
Cooling System	Water cooled	
Displacement	liters 2.216	
Oil consumption	of fuel consumption % 0.1	
Lube oil capacity	10.6 liters	
Coolant capacity	liters (Tropical Radiator) 9.32	
Governor	Mechanical	
Speed	1500 rpm	1800 rpm
Fuel Consumption @ 100% Load	5.3 L/H	6.2 L/H
Fuel Consumption @ 75% Load	4.0 L/H	4.7 L/H
Fuel Consumption @ 50% Load	2.9 L/H	3.4 L/H
Radiator Cooling Air Flow	40.2 m3/min	47.4 m3/min
Max exhaust gas flow	3.94 m3/min	4.76 m3/min
Emissions regulations	EU2007 (EU97/68/EC Stage II) and EPA Tier 4	

The above performance data are valid as per the following specs:

- Diesel Fuel is according to BS2869 Class A2 or equivalent.
- Lubricating oil is according to API CH4 (15W/40).
- The coolant should be 50% antifreeze and 50% distilled water.

## Alternator model Leroy Somer TAL040F

Regulation	± 1 %	
International protection	IP23	
Insulation class	H	
Terminals	6	
Frequency	50 Hz	60 Hz
Coolant Air flow	0.06 m3/s	0.072 m3/s