



LBE GENERATORS

*LBE POWERING YOUR WORLD
anytime. anywhere*


CT-344

Powered By Cummins




MODEL			CT-344
Power Pf.0.8	Standby	kVA	397
		kW	316
	Prime	kVA	344
		kW	275
	Frequency	Hz	60
	Voltage	V	220/380
	Rated speed	rpm	1800

Temperature (Celsius) Derate Curves
Unit: kVA



Altitude (meters) Derate Curves
Unit: kVA



Standard reference Conditions:

Standard reference condition 25°C (77°F) air inlet temp, 100m (328ft) A.S.L 30% relative humidity. Fuel consumption data with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998, Class A2.

Standard Features

- The generator set and its components are prototype-tested, factory-built, and production-tested.
- The generator set complies with ISO 8528-5, Class G3 requirements for transient performance.
- The generator set accepts rated load in one step.
- The 60Hz generator set engine is certified by the Environmental Protection Agency (EPA or MEP) to conform to EU2, EU3 nonroad emissions regulations.(≤560KW)
- A one-year limited warranty covers all systems and components. Two-, five-, and ten-year extended warranties are also available.

Generator Features

- The brushless, rotating-field generator has broadrange reconnectability.
- The pilot-excited, permanent-magnet generator (PMG) provides superior short-circuit capability
- Controllers are available for all applications. See controller features inside.
- The low coolant level shutdown prevents overheating (standard on radiator models only).
- Integral vibration isolation eliminates the need for under-unit vibration spring isolators.
- An electronic, isochronous governor delivers precise frequency regulation.
- Electronic engine controls and a generator microprocessor controller combine to deliver one of the most advanced control systems in today's generator market.



LBE GENERATORS

*LBE POWERING YOUR WORLD
anytime. anywhere*

CT-344

Powered By Cummins

Engine Specifications

QSL9-G5



Fuel Rating	FR96535
Type	4 cycle, in-line, Turbo Charged, Air-cooled
Bore mm	114 mm (4.5 in.)
Stroke mm	145 mm (5.7 in.)
Displacement litre	8.8 litre (543 in. ³)
Cylinder block	6 cylinder
Battery charging alternator	70 amps
Starting voltage	24-volt
Fuel system	Bosch HPCR
Fuel filter	Spin-on fuel filters with water separator
Lube oil filter type(s)	Spin-on full flow filter
Lube oil capacity (l)	26.5
Flywheel dimensions	SAE 1

Coolpac Performance Data

Cooling system design	Air-air Charge Cooled
Coolant ratio	50% ethylene glycol; 50% water
Coolant capacity (l)	36
Limiting ambient temp.** (°C)	50 (50Hz); 55 (60Hz)
Fan power (kWm)	11 (50Hz); 18 (60Hz)
Cooling system air flow (m ³ /s)**	6.1 (50Hz); 7.8 (60Hz)
Air cleaner type	Light Duty Dry replaceable element with restriction indicator

** @ 13mm H₂O

Fuel Consumption 1800 (60Hz)

%	kWm	BHP	L/hr	US Gal. /hr
Standby Power				
100	355	476	89	23.6
Prime Power				
100	307	412	75	19.9
75	231	309	55	14.4
50	154	206	36	9.6
25	77	103	20	5.3
Continuous Power				
100	261	350	63	16.5



LBE GENERATORS

*LBE POWERING YOUR WORLD
anytime. anywhere*

CT-344

Powered By Cummins

ALTERNATOR SPECIFICATION

Type	4-Pole, Rotating-Field
Exciter type	Brushless, Permanent-Magnet, Pilot Exciter
Voltage regulator	Solid-State, Volts/Hz
Insulation	NEMA MG1, Class H
Material	Synthetic, Nonhygroscopic
Temperature rise	Prime 130°C, 150°C Standby
Bearing: quantity, type	1, Sealed
Coupling	Flexible Disc
Amortisseur windings	Full
Rotor balancing	125% 60 Hz, 150% 50 Hz
Voltage regulation, no-load to full-load(with < 0.5% drift due to temp. variation	3-Phase Sensing, $\pm 0.25\%$
One-step load acceptance	100% of Rating
Unbalanced load capability	100% of Rated Standby

- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting.
- Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds.
- Sustained short-circuit current enabling downstream circuit breakers to trip without collapsing the generator field.
- Self-ventilated and drip-proof construction.
- Superior voltage waveform from two-thirds pitch windings and skewed stator.
- Digital solid-state volts-per-hertz voltage regulator with $\pm 0.25\%$ no-load to full-load regulation.
- Brushless alternator with brushless pilot exciter for excellent load response.



LBE GENERATORS

*LBE POWERING YOUR WORLD
anytime. anywhere*

CT-344

Powered By Cummins

Controller

Audiovisual annunciation with NFPA 110 Level 1 capability. Programmable microprocessor logic and digital display features.

Safeguard circuit protection standard.

12- or 24-volt engine electrical system capability.

Remote start, remote annunciation, and remote communication options. Refer to M6-46 for additional controller features and accessories.



Key Features

- 4-line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- LED and LCD alarm indication
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Control logic facilities
- Easy access diagnostic page
- CAN and Magnetic Pick-up / Alt. Sensing
- Fuel usage monitor and low fuel alarms
- Charger alternator failure alarm
- Manual speed control
- Manual fuel pump control
- Engine exerciser
- "protections disabled" feature
- kW overload protection
- Power monitoring
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer
- Unbalanced load protection
- Independent Earth Fault trip
- USB connectivity
- Backed up real time clock
- Configurable display languages
- User selectable RS232 and RS485 communications
- SMS Messaging (additional external modem required)
- Additional display screens to help with modem diagnostics
- Integral PLC editor



LBE GENERATORS

*LBE POWERING YOUR WORLD
anytime. anywhere*

CT-344

Powered By Cummins

Generating Sets Standard and Optional Features

Engine	• 4-stroke, water-cooled diesel engine • Standard air filter • Standard fuel filter • Standard oil filter • Oil temperature sensor • Low coolant level sensor • Radiator with blowing fan • Industrial Grade Silencer • Fuel water separator • Water jacket heater (optional)
Alternator	• Class H insulation • IP23 Protection • Automatic Voltage Regulator (AVR) • PMG excitation (optional) • Single bearing alternator • Class F or class B temperature rise (optional) • Digital Voltage Regulator (optional) • Double bearing (optional) • Anti-Condensation Heater (optional) • IP41 Protection (optional)
Electrical system	• Maintenance-free and anti-explosion battery • Standard breaker • ABB breaker (optional) • ATS (optional) • Battery charger (optional) • GMS monitoring (optional) • 127/230 voltage (optional)
Packing	• Engine manual • Alternator manual • Gensets operation and maintenance manual • Tool kit
Baseframe	• Forklift pockets • Pulling slots • Earth wire protection • Built-in anti vibration mountings • Fuel outlet valve • Standard fuel tank • Enlarged fuel tank (optional) • Separated fuel tank (optional)
Canopy	• Weatherproof & sound-attenuated canopy • Sound-absorbing material • Lifting lug • Emergency stop button • Inside silencer




LBE GENERATORS

CT-344


*LBE POWERING YOUR WORLD
anytime. anywhere*

Powered By Cummins

Overview Dimension & Weight



(Silent type)					
Configuration	L= Length (mm)	W= Width (mm)	H= Height (mm)	Weight (kg)	Fuel Tank Capacity(L)
Silent Type	4260	1462	2100	3990	770



(Open type)					
Configuration	L= Length (mm)	W= Width (mm)	H= Height (mm)	Weight (kg)	Fuel Tank Capacity (L)
Open Type	3370	1250	1950	2900	470



3473 As Sayyidah Khadijah Street – 6461 Al Faisaliyah District
23441 Jeddah, Kingdom Of Saudi Arabia

C.R. 7023514651
VAT No. 310940679600003
Phone 0530371038
E-mail INFO@LBE-KSA.COM
Website WWW.LBE-KSA.COM

٣٤٧٣ شارع السيدة خديجة – ٦٤٦١ حي الفيصلية
٢٣٤٤١ جدة، المملكة العربية السعودية
السجل التجاري ٧٠٢٣٥١٤٦٥١
الرقم الضريبي ٣١٠٩٤٠٦٧٩٦٠٠٠٣
الهاتف ٠٥٣٠٣٧١٠٣٨
بريد الكتروني INFO@LBE-KSA.COM
موقع الكتروني WWW.LBE-KSA.COM